


Código

Confección

Embalaje

R6

Cilindro R6 DOBLE PERFIL, llave plana de latón niquelado con 6 pistones.
Con barra resistente al taladro en el cuerpo del cilindro. Leva DIN 30°. **5 llaves.**
Tornillo 65 mm. Tarjeta de código.
(Llave en bruto código 020839).



L	C + D				
		LATÓN	NÍQUELADO		
L 56 mm.	(28+28)	880928287.5	880928289..5	1	5
L 61 mm.	(28+33)	880928337.5	880928339..5	1	5
L 60 mm.	(30+30)	880930307.5	880930309..5	1	5
L 65 mm.	(30+35)	880930357.5	880930359..5	1	5
L 70 mm.	(30+40)	880930407..5	880930409..5	1	5
	(35+35)	880935357.5	880935359..5	1	5
L 75 mm.	(30+45)	880930457.5	880930459..5	1	5
	(35+40)	880935407.5	880935409..5	1	5
L 80 mm.	(30+50)	880930507.5	880930509..5	1	5
	(35+45)	880935457.5	880935459..5	1	5
	(40+40)	880940407.5	880940409..5	1	5
	(40+45)	880940457.5	880940459..5	1	5
L 85 mm.	(30+55)	880930557.5	880930559..5	1	5
	(35+50)	880935507.5	880935509..5	1	5
	(40+45)	880940457.5	880940459..5	1	5
	(40+50)	880940507.5	880940509..5	1	5
L 90 mm.	(30+60)	880930607.5	880930609..5	1	5
	(35+55)	880935557.5	880935559..5	1	5
	(45+45)	880945457.5	880945459..5	1	5
	(45+50)	880945507.5	880945509..5	1	-
L 95 mm.	(30+65)	880930657.5	880930659..5	1	-
	(35+60)		880935609..5	1	-
	(40+55)	880940557.5	880940559..5	1	-
	(45+50)	880945507.5	880945509..5	1	-
L 100 mm.	(30+70)	880930707.5	880930709..5	1	-
	(35+65)	880935657.5	880935659..5	1	-
	(40+60)	880940607.5	880940609..5	1	-
	(45+55)	880945557.5	880945559..5	1	-
	(50+50)	880950507.5	880950509..5	1	-
L 105 mm.	(30+75)	880930757.5	880930759..5	1	-
	(45+60)	880945607.5	880945609..5	1	-
	(50+55)	880950557.5	880950559..5	1	-
L 110 mm.	(30+80)	880930807.5	880930809..5	1	-
	(35+75)		880935759..5	1	-
	(40+70)	880940707.5	880940709..5	1	-
	(45+65)		880945659..5	1	-
	(50+60)	880950607.5	880950609..5	1	-
L 120 mm.	(60+60)	880960607.5	880960609..5	1	-
	(65+55)	880965557.5	880965559..5	1	-