

# LB3200PW

HIDROLIMPIADORA A GASOLINA  
PETROL HIGH PRESSURE WASHER



by *Tonino Lamborghini*

GARDEN MACHINERY

Ref.: LB3200PW

## ESPECIFICACIONES TÉCNICAS TECHNICAL SPECIFICATIONS

		<b>LB3200PW</b>	
<b>MOTOR ENGINE</b>	Marca	Brand	By Tonino LAMBORGHINI Licensed
	Tipo	Type	OHV
	Cilindrada (cc)	Displacement (cc)	208cc
	Potencia Maxima (kW / hp)	Maximum Power (kW / hp)	4,2kW / 5,6hp
	Potencia Nominal (kW / hp)	Rated power (kW / hp)	4,1kW / 5,4hp
	Arranque	Starter	Manual
	Parachispas	Spark Arrester	Si / Yes
	Sensor de Nivel de Aceite	Oil Level Sensor	Si / Yes
	Depósito de Combustible (l)	Petrol tank (l)	3.6L
	Nivel Sonoro (dB)	Sound Level (dB)	105 dB
<b>BOMBA PUMP</b>	Presión Maxima (PSI - bar)	Maximum Pressure (PSI - bar)	3200psi / 221bar
	Presión Nominal (PSI - bar)	Rated Pressure (PSI - bar)	3100psi / 213bar
	Caudal máximo (l/h)	Maximum flow (l/h)	568 l/h
	Maxima temperatura de agua (°C)	Max. Water temperature (°C)	40 °C
	Temperatura activacion valvula de alivio (°C)	Relief valve opening temperature (°C)	60 °C
	Tipo	Type	Bomba Axial (Horizontal) / Axial Pump (Horizontal)
	Material	Material	Aluminio / Aluminun
	Longitud manguera alta presión (m)	High pressure hose lenght (m)	9,2 m
	Depósito detergente (l)	Detergent Tank (l)	3.5L
	<b>ACCESORIOS ACCESSORIES</b>	Lanza regulable	Regulable lance
Boquilla turbo		Turbo nozzle	Si / Yes
Filtro agua		Water filter	Si / Yes
Depósito detergente		Soap deposit	Si / Yes
Enrollador manguera		Hose reel	No
<b>EMBALAJE PACKING</b>	Dimensiones del producto (mm)	Product dimensions (mm)	602x415x613
	Dimensiones del embalaje (mm)	Packing dimensions (mm)	715x525x1062
	Container loads (20"/40"/40HQ)	Container load (20"/ 40"/ 40HQ)	- / - / 424
	Peso Neto (kg)	Net weight /kg)	27.7 ±2
	Peso Bruto (kg)	Gross weight (kg)	32,9 ±2
EAN	EAN	8434691495517	
<b>OTRAS CARACTERÍSTICAS SPECIFICATIONS</b>	<b>OTHER</b>	Ruedas de transporte Cuenta con Valvula de Alivio por temperatura, para proteger la bomba. 5 boquillas INCLUIDAS (Jabon, 0°, 15°, 25°, 40°)	Transport wheels Equipped with a temperature relief valve to safeguard the pump. INCLUDED 5 Nozzles (Soap, 0°, 15°, 25°, 40°)

